## **Select Mode**



Insert the card into the card reader and a window will pop up called Select Mode. Verify the Keyset and click Select.

## Verify secret codes

Image: Constant of the state of the sta
Refresh Close Help   SW1= SW2=

Click the lock symbol at the top of the screen and verify the secret codes.

GPIN1: 1111

LPIN2: 2222

## **Activate ISIM**



Expand the file tree and right click ISIM. Now click Activition.

Open files and edit									
		1							
File ID 🛆	Short File Name	Long File Name	File Size	File Structure	SFI	EF ARR ID	SE01		
📲 6F02	IMPI	IMS private user identity	149 B	Transparent	02	6F06			
	DOMAIN	Home Network Domain Name	50 B	Transparent	05	6F06			
📲 6F04	IMPU	IMS public user identity	750 B	Linear-fixed	04	6F06			
👰 6F06	ARR	Access Rule Reference	320 B	Linear-fixed	06	6F06			
	IST	ISIM Service Table	1 B	Transparent	07	6F06			
ee 6FAD	AD	Administrative Data	3 B	Transparent	03	6F06			
📲 6FD5	GBABP	molue LISB Smart Card Do:	dor 0 ·	ISHAAF03					
📲 6FD7	GBANL	mptus OSD Smart Card Red	ider 0.	1311/11/03			$\sim$		
	-235	- Interpreted Binary EE information ADE information							
		Home Network Domain Name							
						_			
		ims.cingularme.com	1						
							- 1		
							- 1		
		Update Refresh		Close		Help			
	-				_				

Open the file you want to edit, enter in your information and then click update. DONE!